


BARRIERE PER USO INDUSTRIALE - SERIE CC LIGHT CURTAINS FOR INDUSTRIAL USE - CC SERIES



Dimensioni/Dimensions:



- | | |
|---|--|
| <ul style="list-style-type: none"> • Robusto corpo in alluminio trafilato nero, protezione IP54 • Adatta per funzionamento statico o dinamico • Altissima immunità a disturbi elettromagnetici e luminosi • Uscita a relè 1A con contatto NO/NC • Dip di regolazione della distanza su 4 livelli di portata • Visualizzazione corretto allineamento mediante barra led • Sincronismo filare con protocollo di comunicazione RS485 • Possibilità di collegare fino a 4 barriere alla stessa centralina CTS | <ul style="list-style-type: none"> • Stout aluminium black profile with IP54 degree of protection • Suitable for static and dynamic installations • High immunity against light and electromagnetic interferences • 1A relay output with NO/NC contact • Distance regulation switch on 4 range levels • Correct alignment display through the led bar • Wire synchronism by means of RS485 communication protocol • Connecting up to maximum 4 light curtains to our CTS safety unit |
|---|--|

CARATTERISTICHE TECNICHE/TECHNICAL SPECIFICATIONS

Item	N° raggi/ Beams Q.ty	Risoluzione/ Resolution	Portata/ Operating range	Altezza barriera/ Barrier height	Area protetta/ Protected height	Alimentazione/ Supply voltage	Cavi/ Cables
CC08A	8	100	0 - 8 mt.	1100 mm	da 25 a 725 mm	17-30V DC (230V con centralina di sicurezza opzionale/ Optional 230V safety unit)	Standard 5 mt. (Max 50 mt. su richiesta/ Max 50 mt. on request)
CC12A	12			1500 mm	da 25 a 1125 mm		
CC16A	16			1900 mm	da 25 a 1525 mm		
CC20A	20			2300 mm	da 25 a 1925 mm		
CC24A	24			2700 mm	da 25 a 2325 mm		
CC16B	16	50		1100 mm	da 25 a 775 mm		
CC24B	24			1500 mm	da 25 a 1175 mm		
CC32B	32			1900 mm	da 25 a 1575 mm		
CC40B	40			2300 mm	da 25 a 1975 mm		
CC48B	48			2700 mm	da 25 a 2375 mm		

Accessori/Accessories:

CTS01 = 230V AC



Protezione metallica
opzionale Serie PRO/
Optional PRO series
metallic protection

Serie CTS - Centralina di sicurezza per barriere CC
DIRETTIVA MACCHINE CAT. 2/
CTS Series - Safety unit for CC light curtains
MACHINERY DIRECTIVE LEVEL 2

